

Auto-similarity in rational base number systems

Victor Marsault*,
joint work with Shigeki Akiyama[†] and Jacques Sakarovitch*

*CNRS / Telecom-ParisTech, Paris, France

[†]University of Tsukuba, Japan

WORDS, Turku, Finland

2013-09-17

- 1 From integer base to rational base
- 2 The world of minimal words
- 3 Auto-similarity and derived transducer
- 4 Span of a node

- base $p \geq 2$
- alphabet $A_p = \{0, 1, \dots, p-1\}$

- base $p \geq 2$
- alphabet $A_p = \{0, 1, \dots, p-1\}$
- evaluation $\pi(a_n \cdots a_1 a_0) = \sum_{i=0}^n a_i p^i$
- $\pi(A_p^*) = \mathbb{N}$

- base $p \geq 2$
- alphabet $A_p = \{0, 1, \dots, p-1\}$
- evaluation $\pi(a_n \cdots a_1 a_0) = \sum_{i=0}^n a_i p^i$
- $\pi(A_p^*) = \mathbb{N}$
- representation $\langle n \rangle_p = \langle n' \rangle_p . a$
 - (n', a) is the Euclidean division of n by p .
- $\langle \mathbb{N} \rangle_p = (A_p \setminus \{0\}) \cdot A_p^*$

- a base $\frac{p}{q}$ with $p > q$ and p coprime with q
- representation $\langle n \rangle_{\frac{p}{q}} = \langle n' \rangle_{\frac{p}{q}} . a :$
 - (n', a) is the Euclidean division of $(q \times n)$ by p .

- a base $\frac{p}{q}$ with $p > q$ and p coprime with q
- representation $\langle n \rangle_{\frac{p}{q}} = \langle n' \rangle_{\frac{p}{q}}.a :$
 - (n', a) is the Euclidean division of $(q \times n)$ by p .

Example: computation of $\langle 3 \rangle_{\frac{3}{2}}$:

$$\langle 3 \rangle_{\frac{3}{2}} =$$

- a base $\frac{p}{q}$ with $p > q$ and p coprime with q
- representation $\langle n \rangle_{\frac{p}{q}} = \langle n' \rangle_{\frac{p}{q}}.a :$
 - (n', a) is the Euclidean division of $(q \times n)$ by p .

Example: computation of $\langle 3 \rangle_{\frac{3}{2}}$:

$$\langle 3 \rangle_{\frac{3}{2}} =$$

$$\begin{array}{c} \boxed{2} \times \boxed{3} = \boxed{3} \times N_1 + a_0; \\ \uparrow \quad \quad \uparrow \quad \quad \uparrow \\ q \quad \quad n \quad \quad p \end{array}$$

- a base $\frac{p}{q}$ with $p > q$ and p coprime with q
- representation $\langle n \rangle_{\frac{p}{q}} = \langle n' \rangle_{\frac{p}{q}}.a :$
 - (n', a) is the Euclidean division of $(q \times n)$ by p .

Example: computation of $\langle 3 \rangle_{\frac{3}{2}}$:

$$\langle 3 \rangle_{\frac{3}{2}} =$$

$$2 \times 3 = 3 \times N_1 + a_0; \quad \Rightarrow N_1 = 2 \text{ and } a_0 = 0.$$

- a base $\frac{p}{q}$ with $p > q$ and p coprime with q
- representation $\langle n \rangle_{\frac{p}{q}} = \langle n' \rangle_{\frac{p}{q}}.a :$
 - (n', a) is the Euclidean division of $(q \times n)$ by p .

Example: computation of $\langle 3 \rangle_{\frac{3}{2}}$:

$$\langle 3 \rangle_{\frac{3}{2}} = \langle 2 \rangle_{\frac{3}{2}} 0 =$$

- a base $\frac{p}{q}$ with $p > q$ and p coprime with q
- representation $\langle n \rangle_{\frac{p}{q}} = \langle n' \rangle_{\frac{p}{q}}.a :$
 - (n', a) is the Euclidean division of $(q \times n)$ by p .

Example: computation of $\langle 3 \rangle_{\frac{3}{2}}$:

$$\langle 3 \rangle_{\frac{3}{2}} = \langle 2 \rangle_{\frac{3}{2}} 0 =$$

$$2 \times 2 = 3 \times N_2 + a_1;$$

- a base $\frac{p}{q}$ with $p > q$ and p coprime with q
- representation $\langle n \rangle_{\frac{p}{q}} = \langle n' \rangle_{\frac{p}{q}}.a :$
 - (n', a) is the Euclidean division of $(q \times n)$ by p .

Example: computation of $\langle 3 \rangle_{\frac{3}{2}}$:

$$\langle 3 \rangle_{\frac{3}{2}} = \langle 2 \rangle_{\frac{3}{2}} 0 =$$

$$2 \times 2 = 3 \times N_2 + a_1; \quad \Rightarrow N_2 = 1 \text{ and } a_1 = 1.$$

- a base $\frac{p}{q}$ with $p > q$ and p coprime with q
- representation $\langle n \rangle_{\frac{p}{q}} = \langle n' \rangle_{\frac{p}{q}}.a :$
 - (n', a) is the Euclidean division of $(q \times n)$ by p .

Example: computation of $\langle 3 \rangle_{\frac{3}{2}}$:

$$\langle 3 \rangle_{\frac{3}{2}} = \langle 2 \rangle_{\frac{3}{2}} 0 = \langle 1 \rangle_{\frac{3}{2}} 10 =$$

- a base $\frac{p}{q}$ with $p > q$ and p coprime with q
- representation $\langle n \rangle_{\frac{p}{q}} = \langle n' \rangle_{\frac{p}{q}} . a :$
 - (n', a) is the Euclidean division of $(q \times n)$ by p .

Example: computation of $\langle 3 \rangle_{\frac{3}{2}}$:

$$\langle 3 \rangle_{\frac{3}{2}} = \langle 2 \rangle_{\frac{3}{2}} 0 = \langle 1 \rangle_{\frac{3}{2}} 10 =$$

$$2 \times 1 = 3 \times N_3 + a_2;$$

- a base $\frac{p}{q}$ with $p > q$ and p coprime with q
- representation $\langle n \rangle_{\frac{p}{q}} = \langle n' \rangle_{\frac{p}{q}}.a :$
 - (n', a) is the Euclidean division of $(q \times n)$ by p .

Example: computation of $\langle 3 \rangle_{\frac{3}{2}}$:

$$\langle 3 \rangle_{\frac{3}{2}} = \langle 2 \rangle_{\frac{3}{2}} 0 = \langle 1 \rangle_{\frac{3}{2}} 10 =$$

$$2 \times 1 = 3 \times N_3 + a_2; \quad \Rightarrow N_3 = 0 \text{ and } a_2 = 2.$$

- a base $\frac{p}{q}$ with $p > q$ and p coprime with q
- representation $\langle n \rangle_{\frac{p}{q}} = \langle n' \rangle_{\frac{p}{q}}.a :$
 - (n', a) is the Euclidean division of $(q \times n)$ by p .

Example: computation of $\langle 3 \rangle_{\frac{3}{2}}$:


$$\langle 3 \rangle_{\frac{3}{2}} = \langle 2 \rangle_{\frac{3}{2}} 0 = \langle 1 \rangle_{\frac{3}{2}} 10 = 210$$

- a base $\frac{p}{q}$ with $p > q$ and p coprime with q
- alphabet $A_p = \{0, 1, \dots, p-1\}$
- representation $\langle n \rangle_{\frac{p}{q}} = \langle n' \rangle_{\frac{p}{q}}.a :$
 - (n', a) is the Euclidean division of $(q \times n)$ by p .
- $L_{\frac{p}{q}} = \langle \mathbb{N} \rangle_{\frac{p}{q}}$


- a base $\frac{p}{q}$ with $p > q$ and p coprime with q
- alphabet $A_p = \{0, 1, \dots, p-1\}$
- representation $\langle n \rangle_{\frac{p}{q}} = \langle n' \rangle_{\frac{p}{q}}.a :$
 - (n', a) is the Euclidean division of $(q \times n)$ by p .
- $L_{\frac{p}{q}} = \langle \mathbb{N} \rangle_{\frac{p}{q}}$
- evaluation $\pi(a_n \cdots a_1 a_0) = \sum_{i=0}^n (\frac{a_i}{q})(\frac{p}{q})^i$

- a base $\frac{p}{q}$ with $p > q$ and p coprime with q
- alphabet $A_p = \{0, 1, \dots, p-1\}$
- representation $\langle n \rangle_{\frac{p}{q}} = \langle n' \rangle_{\frac{p}{q}}.a$:
 - (n', a) is the Euclidean division of $(q \times n)$ by p .
- $L_{\frac{p}{q}} = \langle \mathbb{N} \rangle_{\frac{p}{q}}$
- evaluation $\pi(a_n \cdots a_1 a_0) = \sum_{i=0}^n (\frac{a_i}{q})(\frac{p}{q})^i$
 - if $\pi(u) = n \in \mathbb{N}$, u is of the form $0^k \langle n \rangle$
 - $\mathbb{N} \subsetneq \pi(A_p^*) \subsetneq \mathbb{Q}$


- $L_{\frac{p}{q}}$ is prefix-closed and right-extendable.



- $L_{\frac{p}{q}}$ is prefix-closed and right-extendable.
- $L_{\frac{p}{q}}$ is not rational (not even context-free) [AFS'08].




- $T_{\frac{p}{q}}$ accepts $0^*L_{\frac{p}{q}}$ (that is, the words u such that $\pi(u) \in \mathbb{N}$)



- 1 From integer base to rational base
- 2 The world of minimal words
- 3 Auto-similarity and derived transducer
- 4 Span of a node

w_n : the (infinite) word starting from n taking the lowest branch.



Given an integer n , the minimal word w_n is

- over the alphabet $\{0, \dots, (q-1)\} = A_q$
- the unique word over A_q readable from n

Given an integer n , the minimal word w_n is

- over the alphabet $\{0, \dots, (q-1)\} = A_q$
- the unique word over A_q readable from n

Proposition [AFS'08]

w_n and w_m have the same prefix of length k .

$$\begin{array}{c} \Updownarrow \\ n \equiv m [q^k] \end{array}$$

Given an integer n , the minimal word w_n is

- over the alphabet $\{0, \dots, (q-1)\} = A_q$
- the unique word over A_q readable from n
- different from w_m (for $m \neq n$)
- aperiodic

Proposition [AFS'08]

w_n and w_m have the same prefix of length k .

$$\begin{array}{c} \Updownarrow \\ n \equiv m [q^k] \end{array}$$

W : the set of minimal words.

Topological properties

- The topological closure of W is A_q^ω whole.
- The interior of W is *empty*.

Shift operation

- W is stable by shift
- W cannot be finitely generated through shift.

$$\begin{array}{ccc} \gamma : A_q^\omega & \longrightarrow & A_q^\omega \\ w_n & \longmapsto & w_{n+1} \end{array}$$


$$\begin{array}{ccc} \gamma : A_q^\omega & \longrightarrow & A_q^\omega \\ w_n & \longmapsto & w_{n+1} \end{array}$$

Remark

$w_n = a.w_{n+p}$ for some letter a and integer p .
(Or, equivalently $\gamma^p(w_n)$ is the shifted of w_n .)


- 1 From integer base to rational base
- 2 The world of minimal words
- 3 Auto-similarity and derived transducer
- 4 Span of a node

Derived transducer for $\frac{3}{2}$: $D_{\frac{3}{2}}$



A simple label substitution...

10

 $0 \longleftrightarrow 1|0$ $1 \longleftrightarrow 0|0, 1|1$ $2 \longleftrightarrow 0|1$ 

Proposition

If $p = 2q - 1$,

- the underlying graph of $D_{\frac{p}{q}}$ and $T_{\frac{p}{q}}$ are identical;
- the labels of the transitions of $D_{\frac{p}{q}}$ are obtained by an (injective) substitution from those of $T_{\frac{p}{q}}$.

Proposition

If $p = 2q - 1$,

- the underlying graph of $D_{\frac{p}{q}}$ and $T_{\frac{p}{q}}$ are identical;
- the labels of the transitions of $D_{\frac{p}{q}}$ are obtained by an (injective) substitution from those of $T_{\frac{p}{q}}$.

Theorem

The derived transducer $D_{\frac{p}{q}}$ is locally computable from $T_{\frac{p}{q}}$.

Step 1: changing the alphabet

$$A_p \longrightarrow B_{p,q} = \{p - (2q - 1), \dots, p - 1\}$$

- $B_{p,q}$ always has $(2q - 1)$ elements
- The maximal element of A_p and $B_{p,q}$ are the same.

Step 1: changing the alphabet


$$A_p \longrightarrow B_{p,q} = \{p - (2q - 1), \dots, p - 1\}$$

- $B_{p,q}$ always has $(2q - 1)$ elements
 - The maximal element of A_p and $B_{p,q}$ are the same.
-
- if $p = (2q - 1)$, $A_p = B_{p,q}$
 - if $p < (2q - 1)$, $A_p \subseteq B_{p,q}$ (the base $\frac{p}{q}$ is “too small”)
 - if $p > (2q - 1)$, $A_p \supseteq B_{p,q}$ (the base $\frac{p}{q}$ is “too big”)


Example of the “small” base $\frac{4}{3}$ (Step 1)

13

$$\blacksquare A_4 = \{0, 1, 2, 3\} \subseteq \{-1, 0, 1, 2, 3\} = B_{4,3}$$



$$\blacksquare A_4 = \{0, 1, 2, 3\} \subseteq \{-1, 0, 1, 2, 3\} = B_{4,3}$$


 $\hat{T}_{\frac{4}{3}}$

Step 1: changing the alphabet


$$A_p \longrightarrow B_{p,q} = \{p - (2q - 1), \dots, p - 1\}$$

Step 2: changing the labels

$$\begin{aligned} \omega : B_{p,q} &\longrightarrow \mathbb{P}(A_p \times A_p) \\ a &\longmapsto \{(b|c) \mid (b - c) = \underbrace{a - (p - q)}_{\text{distance to the center of B}}\} \end{aligned}$$


Example of the “small” base $\frac{4}{3}$ (Step 2)

15




Example of the “big” base $\frac{7}{3}$ (Step 1)

■ $A_7 = \{0, 1, 2, 3, 4, 5, 6\} \supseteq \{2, 3, 4, 5, 6\} = B_{7,3}$




Example of the “big” base $\frac{7}{3}$ (Step 1)

■ $A_7 = \{0, 1, 2, 3, 4, 5, 6\} \supseteq \{2, 3, 4, 5, 6\} = B_{7,3}$




Example of the “big” base $\frac{7}{3}$ (Step 2)

$2 \rightarrow 2|0$
 $3 \rightarrow 1|0, 2|1$
 $4 \rightarrow 0|0, 1|1, 2|2$
 $5 \rightarrow 0|1, 1|2$
 $6 \rightarrow 0|2$




- 1 From integer base to rational base
- 2 The world of minimal words
- 3 Auto-similarity and derived transducer
- 4 Span of a node

$$\rho(a_1 a_2 \cdots a_n \cdots) = \sum_{i \geq 0} \frac{a_i}{q} \left(\frac{p}{q} \right)^{-i}.$$



Definition – span of the node X

The length of the interval reachable from X in the tree.



Definition – span of the node X

The length of the interval reachable from X in the tree.

Definition – renormalised span of the node X

the span of X multiplied by $(\frac{p}{q})^k$, where k is the depth of X .

$S_{\frac{p}{q}}$ denotes the set of the renormalised span of every node.

Definition

- The span of n is represented by the word $(w'_n \ominus w_n)$, where:
 - w'_n is the *maximal* word starting from n ;
 - “ \ominus ” denotes the digit-wise subtraction.
(Example : $321 \ominus 012 = 31(-1)$)
- It is called the *span-word* of n and is over the alphabet $B_{p,q}$.

Definition

- The span of n is represented by the word $(w'_n \ominus w_n)$, where:
 - w'_n is the *maximal* word starting from n ;
 - “ \ominus ” denotes the digit-wise subtraction.
(Example : $321 \ominus 012 = 31(-1)$)
- It is called the *span-word* of n and is over the alphabet $B_{p,q}$.

Proposition

$\hat{T}_{\frac{p}{q}}$ accepts the topological closure of the language of the span-words.

Theorem

- If $p \leq 2q - 1$, $S_{\frac{p}{q}}$ is dense.
- If $p > 2q - 1$, $S_{\frac{p}{q}}$ is nowhere dense.

- The derived transducer somehow requires the same structure as the original tree.
- The topological properties of the set of spans divides the rational base number systems in two classes.
- The cases $p = 2q - 1$ is remarkable in both constructions.

Next question

For a given integer n ,
is there a *finite* transducer realising $w_n \mapsto w_{n+1}$?